A photograph of the interior of the Large Hadron Collider (LHC) tunnel. The tunnel is a large, circular concrete structure with a high ceiling. On the left, there are several large, blue cylindrical components, likely part of the particle detectors. The ceiling is supported by a complex network of steel beams and pipes. Orange safety lights are mounted on the ceiling and walls. In the distance, a red fire extinguisher is mounted on the wall. The overall atmosphere is industrial and technical.

LHC and HL-LHC

O. Brüning  
CERN, Geneva, Switzerland

## Contents:

- LHC design aspects and physics goals → **Synchrotron as the HEP workhorse**
- Technology Challenges → **Superconducting magnet performance reach**
- Luminosity optimization
  - ➔ **Operational challenges and limitations**
  - ➔ **Machine efficiency and Turnaround Time**
  - ➔ **Beam power and damage potential ➔ Machine Protection**
  - ➔ **Operational challenges**
- Operation experience: **Unexpected Obstacles**

# Accelerators for Particle Physics Recap

■ Collider Particle types:

Leptons:

‘true’ elementary particles → well defined Center of Mass [CM] collision energy  
(precision measurement)

‘light’ particles ( $\gamma \gg 1$ ) → strong synchrotron radiation  
(size, damping, magnet type, limitation in energy reach)


Hadrons:

Composite particle collisions → range of CM energies  
(discovery potential ← → background)

‘heavy’ particles → suppressed synchrotron radiation  
(superconducting magnet technology, energy reach)

# Accelerators for Particle Physics Recap

- collider ring design requires 2 beams:



- design with one aperture requires particles & anti-particles
  - Not efficient for a hadron collider! (e.g. Tevatron, Chicago USA)
  - But attractive for lepton colliders [LEP and Super KEK-B]
- 2-ring design implies twice the hardware
  - Allows higher beam intensities, more bunches and different particle species
  - But more costly and potentially higher failure rate!

## Key Goals of the LHC collider:


- Unitarity crisis of the Standard Model → SM predictions yield over 100% probabilities in W-W interactions @ 1TeV CM collision energies without Higgs particle
  - Probe 1TeV CM collision regime and look for SM discrepancies, or find the Higgs
  - Higgs mass was not known → need to cover a wide range of CM collision Energies!
- Challenges
  - Small cross section events require large luminosity! →  $L > 10^{33} \text{ cm}^{-2} \text{ s}^{-1}$
  - As the mass of the Higgs was not known when the LHC was designed, one wants to cover a wide range of collision energies → proton-proton collider
- Competition with Superconducting Super Collider in the US [80km circumference]
  - LHC study was pushed in competition with the SSC
    - re-use of the existing LEP tunnel and novel, compact magnet design!
  - Needed to be substantially lower cost than the SSC

## Synchrotron concept: Work Horse for most HEP colliders

■  $R = \text{constant}$ :

$$v = c \rightarrow B \propto \gamma$$

$$r = \frac{m_0}{q} \cdot \frac{\gamma}{B} \cdot v$$



## Synchrotron: magnet technology

■ uniform B field:  $R = \text{constant}$

$$p = q \cdot \frac{B \cdot \text{circ}}{2\pi} \approx E / c$$

for  $E \gg E_0$

■ realistic synchrotron: B-field is not uniform

- drift space for installation
- different types of magnets
- space for experiments etc


$$E = \frac{q \cdot c}{2\pi} \cdot \oint B \cdot ds$$

→ high beam energies require:


- high magnetic bending field
- large circumference
- large packing factor



# Magnet aperture: Beam size in a FODO Lattice:

Optics: Overall focusing with alternate setup of focusing and de-focusing lenses → quadrupole magnets are the electro-magnetic lenses for particle beams



Ellipse area in  $(x, x')$  plane



Amplitude  Phase 

$$x(s) = A\sqrt{\beta_x(s)} \cos(\phi(s) + \phi_0)$$

Emittance shrinks naturally as we go up in energy

Normalized emittance  
(give or take blow-up from other sources)  
remains constant

$$\mathcal{E}_n = \beta \gamma \mathcal{E}$$

# Compromise between Bending and Focusing Fields

The aperture of a dipole magnet influences the maximum field strength:

- A smaller aperture allows for a stronger magnetic field for the same current in the coils
  - Formulated differently: providing a given magnetic field in a larger aperture requires more current which requires more coil layers once the maximum acceptable current in the conductor has been reached → higher cost for the magnet production
- The stored energy in a magnetic field is proportional to the square of the magnetic field and the volume of the field → more challenging requirements for the machine protection


Optimizing the design of accelerator dipole magnets:

- Minimize the required aperture to allow for:  
A maximum field at acceptable stored energies and acc

Balanced compromise for giving space for quadrupole and dipole magnets!

# LHC Arc-Cell Layout


Maximize the space occupied by dipole magnet while providing sufficient focusing to keep the magnet aperture acceptable



- Three 15 meter long dipole magnets per 3.4 meter long quadrupole magnet; plus space for dipole and non-linear corrector magnets → Packing factor of ca. 80%


## Maximizing the dipole 'Fill Factor'

- 15 m long, 30 Ton  
difficult transport &  
tight tolerances for  
installation




# Magnet Technology

■ 2-in-1 dipole magnet design with common infrastructure:



LHC DIPOLE : STANDARD CROSS-SECTION



-15 m long

→ few interconnects (high filling factor)

- compact 2-in-1 design → allows p-p collisions in LEP tunnel
- corrector magnets at ends → tight mechanical tolerances

## Challenges: magnet technology limit

- LHC physics goal: 1 TeV CME  $\rightarrow$  > 5 TeV beam energy  $\rightarrow$  7TeV design
- existing infrastructure: LEP tunnel: circ = 27 km (ca. 17mi)  
with 22 km arcs (ca. 14mi)
- assume 80% of arcs can be filled with dipole magnets:  $F = 0.8$
- required dipole field for the LHC:


$$\frac{2\pi}{q} \cdot \frac{E / c}{circ \cdot F} = B \quad \rightarrow \quad B = 8.38 \text{ T}$$

(earth:  $0.3 \cdot 10^{-4} \text{ T}$ )

# Magnet Technology Re-Cap


high beam energies require large rings and high fields

## 1) Iron joke magnet design



- field quality given by pole face geometry
- field amplified by Ferromagnetic material
- iron saturates at 2 T
- Ohmic losses for high magnet currents


## 2) air coil magnet design



- field quality given by coil geometry
- SC technology avoids Ohmic losses
- not always superconducting → risk of magnet quenches
- field quality changes with time

# Introduction: Magnet Technology

- LHC Dipole Magnets: 8.3T, with 11850A → not possible with Cu  
→ superconductor, but with high ambient magnetic field > 8 T @ coil



- 1.9 K cooling with superfluid He (thermal conductivity)
- current density of 2.75 kA / mm<sup>2</sup>

At the limit of NbTi technology (HERA & Tevatron ca. 5 T @ 2kA/mm<sup>2</sup>)!!

LHC Magnet Technology:  
Thousands of fine Nb-Ti filaments well  
separated along km of wires  
Industrial production via extrusion


Fine filaments of Nb-Ti in a Cu matrix (for an LHC dipole wire)

Cable of 15 kA!

Multi-wire cable: the way to 10-100 kA!

# Superconducting Magnet Challenges: Field Quality

- SC Rutherford cable in transverse field



- The eddy currents loops generate a magnetic field that adds (“*field advance*”) to the background field inside the aperture, proportional to:  $dB/dt$  and  $1/R_c$
- Current ramps induce field distortions for all harmonics  $\Delta b^{rr}_n$ ,  $\Delta a^{rr}_n$
- Minimum specified **Rc** value for the machine  $\sim 15 \mu\Omega$  which gives (estimation):
  - $b_1=6$  units
  - $b_2=15$  units
  - multipoles errors  $\sim 0.1-1$  units


1 unit =  $10^{-4}$  of the main field

## Field Imperfections: Super Conducting Magnets



time varying field errors in super conducting magnets

Luca Bottura CERN, AT-MAS

Beam stability requires Field Quality of a few units  
→ Black circle on the right



# LHC (Large Hadron Collider): Magnet Technology



→ The LHC dipole magnets mark the culmination of 30 years of superconducting NbTi magnet technology development!

→ Requiring 1.9K [-271 degrees Celsius] operating temperature


# Accelerators for Particle Physics


## Livingston Plot:

Accelerator energy:

Energy reach has increased exponentially for over 40 years during the last century!!

- Foundation for the Standard Modell Triumph
- Performance increase seems to have slowed down over last decades!






1720 Power converters  
 > 9000 magnetic elements  
 7568 Quench detection systems  
 1088 Beam position monitors  
 4000 Beam loss monitors

150 tonnes Helium, ~90 tonnes at 1.9 K  
 140 MJ stored beam energy in 2012  
**370 MJ design and > 700 MJ for HL-LHC!**  
 830 MJ magnetic energy per sector at 6.5 TeV  
**→ ≈ 10 GJ total @ 7 TeV**


# LEP Design Report 1984



LHC: was already  
1989 to 2000



Start of LEP



ADRON COLLIDER  
E LEP TUNNEL  
Vol. I  
THE ECFA-CERN WORKSHOP  
at Lausanne and Geneva,  
21-27 March 1984

Lausanne  
ECFA-CERN  
Workshop  
1984

Oliver Brüning CERN

22

# LHC (Large Hadron Collider)

**14 TeV proton-proton  
accelerator-collider built in the  
LEP tunnel**

Lead-Lead (Lead-proton) collisions

- 1983 : First studies for the LHC project
- 1988 : First magnet model (feasibility)
- 1994 : Approval by the CERN Council
- 1996-1999 : Series production industrialisation
- 1998 : Declaration of Public Utility & Start of civil engineering
- 1998-2000 : Placement of main production contracts
- 2004 : Start of the LHC installation
- 2005-2007 : Magnets Installation in the tunnel
- 2006-2008 : Hardware commissioning
- 2008-2009 : Beam commissioning and repair
- 2010-2026 : Physics exploitation



Ca. 20 years magnet development!!!



Ca. 30 years machine development!!!

➔ Significant Time scale extending well beyond that of a physicist career!!!

## LHC Performance Measures:

■ Collision energy: e.g. LHC: probing limits of SM;  $E_{CM} > 1 \text{ TeV}$

$p$  collisions  $\rightarrow E_{beam} > 5 \text{ TeV} \rightarrow \text{LHC: } E = 7 \text{ TeV}$

■ Instantaneous luminosity:  $\# \text{ events in detector} = L \cdot \sigma_{event}$


rare events  $\rightarrow L > 10^{33} \text{ cm}^{-2} \text{ sec}^{-1} \rightarrow L = 10^{34} \text{ cm}^{-2} \text{ sec}^{-1}$

■ Integrated luminosity:  $L = \int L(t) dt$

depends on the beam lifetime, the LHC cycle and ‘turn around’ time and overall accelerator efficiency  $\rightarrow$  designed for  $300 \text{ fbarn}^{-1}!!!$


[ca. 20 times the previously existing world production of hadronic collisions!]

# Peak luminosities of Hadron colliders



# LHC in the Geneva Basin and its Experiments






# Luminosity

colliding bunches:

$$L = \frac{n_b \cdot N_1 \cdot N_2 \cdot f_{rev}}{A}$$



$$A = 4\pi \cdot \sigma_x \cdot \sigma_y \quad \text{with:} \quad \sigma = \sqrt{\beta \cdot \epsilon}$$

$N$  = bunch population

$n_b$  = number of bunches

$f_{rev}$  = revolution frequency

$\sigma_{x,y}$  = colliding beam sizes

$F$  = geometric factor

$\beta$  is determined by the magnet arrangement & powering

$\epsilon = \epsilon_n / \gamma$   $\epsilon_n$  is determined by the injector chain

goal:



high bunch intensity and many bunches  
small  $\beta$  at IP and high collision energy

$$L = 10^{34} \text{ cm}^{-2} \text{ sec}^{-1}$$

## Performance optimization: Peak Luminosity

### ■ Luminosity recipe (round beams):


$$L = \frac{n_b \cdot N_1 \cdot N_2 \cdot \gamma \cdot f_{rev}}{4\pi \cdot \beta^* \cdot \varepsilon_n} \cdot F(\phi, \beta^*, \varepsilon, \sigma_s)$$

- 1) maximize bunch intensities → Injector complex & Losses and collimation
- 2) minimize the beam emittance
- 3) minimize beam size (constant beam power) → magnet aperture
- 4) maximize number of bunches (beam power) → X-ing angle
- 5) compensate for ‘F’ → Crab Cavities
- 6) Improve machine ‘Efficiency’ → Minimize number of beam aborts and maximize luminosity lifetime!

# The LHC is NOT a Standalone Machine

The LHC performance fully relies on the **performance of its injector complex**


- By itself **one of the largest accelerator facility in the world** with its own diverse and, for many aspects, unique physics program



- **LHC :  $2 \times (0.45 - 7)$  TeV**
- **SPS : 26 – 450 GeV**  
[RF Power]
- **PS : 2.426 GeV**  
[RF and powering]
- **PSB : 0.06 - 2.4 GeV**
- **Linac 2: 0-500 MeV H<sup>-</sup>**  
Oliver Brüning CERN

## Luminosity Optimization: Crossing Angle I


### ■ Insertion Layout:



### ■ Parasitic bunch encounters:

Operation with ca. 2800 bunches @ 25ns spacing  
→ approximately 30 unwanted collision per  
Interaction Region (IR).

→ Operation requires crossing angle



### ■ non-linear fields from long-range beam-beam interaction:


efficient operation requires large beam separation at unwanted collision points

→ Separation of  $10 - 12 \sigma$  → luminosity reduction and magnet aperture!!!

## Luminosity Optimization: geometric reduction

■ Geometric Luminosity Reduction Factor:

$$F = \frac{1}{\sqrt{1 + \Theta^2}}; \quad \Theta \equiv \frac{\theta_c \sigma_z}{2 \sigma_x}$$



## Luminosity optimization: Beam Lifetime

■ Fill length:

$$\frac{dN_{tot}}{dt} = -n_{IP} \cdot \sigma_{tot} \cdot L \quad \rightarrow \quad \tau_{eff} = \frac{N_{tot}}{n_{IP} \cdot \sigma_{tot} \cdot L_0}$$


■ Example LHC:  $\sigma_{tot} \approx 100\text{mbarn}$  [ $10^{-25}\text{cm}^2$ ]; 2 IPs;  $N_{tot} \approx 3 \cdot 10^{14}$

Nominal Luminosity:  $L_0 = 10^{34} \text{ cm}^{-2} \text{ s}^{-1} \rightarrow \tau_{eff} \approx 42 \text{ hours}$


10 x Luminosity:  $L_0 = 10^{35} \text{ cm}^{-2} \text{ s}^{-1} \rightarrow \tau_{eff} \approx 4 \text{ hours}$

→ Efficient operation requires that the average fill length [data taking for physics] is significantly longer than the time required for preparing a new fill for physics!!!

# Machine Efficiency



## LHC Operations Cycle Run 2



## Energy management challenges: Example LHC

Worry about beam losses:

Failure Scenarios → Local beam Impact

→ Equipment damage

Lifetime & Loss Spikes → Distributed losses

→ Magnet Quench & QPS

→ Machine efficiency



e.g. Cryo Sectors: 95% availability requires 99% with 8 sectors

LHC 8 Sectors → Larger machine [12 Sectors → 20 Sectors]

---


$$1 \text{ electron volt} = 1,602 \times 10^{-19} \text{ joule}$$



# Beam Dump Dilution System



# Assure high machine efficiency by protecting cold magnets

- **Collimation** is designed to provide **cleaning efficiencies  $> 99.99\%$** 
  - *need good statistical accuracy at limiting loss locations;*
  - *simulate only halo particles that interact with collimators, not the core.*
- Design challenge:
  - *59 collimator per beam along 27 km; multi-stage cleaning;*
  - *2 jaw design for 3 collimation planes: horizontal, vertical and skew;*
  - *impact parameters in the sub-micron range;*
  - *beam proton scattering with different collimator materials.*





# LHC collimation system layout

Two warm cleaning insertions,  
3 collimation planes

## IR3: Momentum cleaning

- 1 primary (H)
- 4 secondary (H)
- 4 shower abs. (H,V)

## IR7: Betatron cleaning

- 3 primary (H,V,S)
- 11 secondary (H,V,S)
- 5 shower abs. (H,V)

## Local cleaning at triplets

- 8 tertiary (2 per IP)

Passive absorbers for warm magnets


Physics debris absorbers


Transfer lines (13 collimators)

Injection and dump protection (10)


Total of 118 collimators  
(108 movable).

Two jaws (4 motors) per collimator!







## Transverse cuts from H, V and S primary collimators in IR7




# Operational Experience - 2008 Incident → Interconnects




## Magnet Interconnections:



# 2008 Incident: Busbar splice




## Joint Quality:



Solder used to solder joint had ~~the same~~ melting temperature  
as solder used to pot cable in stabilizer  
⇒ **Solder wicked away from cable**

## Magnet Interconnections:




## 2008 Incident: Collateral Damage



## 2008 Incident: Collateral Damage





## The LHC repairs in detail

14 quadrupole magnets replaced

39 dipole magnets replaced

54 electrical interconnections fully repaired. 150 more needing only partial repairs


Over 4 km of vacuum beam tube cleaned

Re-Start of the machine in 2010 but at lower beam energy to minimize risk of similar events until full consolidation could be implemented


A new longitudinal restraining system is being fitted to 50 quadrupole magnets

Nearly 900 new helium pressure release ports are being installed around the machine

6500 new detectors are being added to the magnet protection system, requiring 250 km of cables to be laid



# Accelerator Vacuum Requirements



Main gases desorbed from vacuum surface are:  
 $\text{H}_2$ ;  $\text{CH}_4$ ;  $\text{CO}$ ;  $\text{CO}_2$ ;  $\text{H}_2\text{O}$  and noble gases

Ultra-High  $< 10^{-7} \text{ Pa} @ 5\text{K}$   
Vacuum  $< 10^{-9} \text{ Pa} @ 293\text{K}$


[ $1 \text{ Pa} = 0.0075 \text{ Torr}$ ]

Ideal Gas:  $P \cdot V = n \cdot R \cdot T$  [R =  $8.31 \text{ J mol}^{-1} \text{ K}^{-1}$ ; n = amount of substance in moles]

$10^{-9} \text{ Pa} @ 293\text{K} \rightarrow 2.4 \cdot 10^{11} \text{ molecules / m}^3$ ;  $10^{-7} \text{ Pa} @ 5\text{K} \rightarrow 1.5 \cdot 10^{15} \text{ molecules / m}^3$

→ The pressure in the LHC beam pipes is about one hundred times lower than on the Moon  
→ **It is the emptiest space in the Solar System!**

# Accelerator Vacuum Requirements



Main gases desorbed from vacuum surface are:  
 $\text{H}_2$ ;  $\text{CH}_4$ ;  $\text{CO}$ ;  $\text{CO}_2$ ;  $\text{H}_2\text{O}$  and noble gases

Plus photons from  
Black Body radiation and Synchrotron Radiation


## Example LEP

Ultra-High Vacuum  $< 10^{-7} \text{ Pa} @ 5\text{K}$   
 $< 10^{-9} \text{ Pa} @ 293\text{K}$


[ $1 \text{ Pa} = 0.0075 \text{ Torr}$ ]

<b>Beam Gas <math>10^{-10} \text{ Torr}</math></b>	$\tau_g = 200 \text{ hours}$
<b>Beam thermal photons</b>	$\tau_{tp} = 80 \text{ hours}$
<b>Beam synchrotron photons</b>	$\tau_{sp} = 134 \text{ hours}$
<b>Total</b>	$\tau_{tot} = 40 \text{ hours}$

# LHC Beam Screen Concept



Cryo Pump



Cooled at 5K to 20K

Delicate Impedance evaluations!

→ Random slot distribution

# Synchrotron: Synchrotron Radiation

■ Quantum Picture:



→ -radiation fan in the bending plane

-opening angle  $\propto \frac{1}{\gamma}$

$$\text{● } P \propto \frac{\gamma^4}{\rho^2} \cdot q^2 \cdot N$$

$$\text{● } \langle E_\gamma \rangle \propto \frac{\gamma^3}{\rho}$$

● polarized



## Synchrotron: Synchrotron Radiation

■ Examples:

X-rays

$\gamma$ -rays

UV light



	$E$ [GeV]	$\rho$ [km]	$N$ [ $10^{12}$ ]	$U$ [MeV]	$P$ [MW]	$E_\gamma$ [keV]
<b>LEP 1</b>	<b>45</b>	<b>3.1</b>	<b>4.7</b>	<b>260</b>	<b>2.1</b>	<b>90</b>
<b>LEP 2</b>	<b>100</b>	<b>3.1</b>	<b>4.7</b>	<b>2800</b>	<b>23</b>	<b>715</b>
<b>LHC</b>	<b>7000</b>	<b>3.1</b>	<b>312</b>	<b>0.007</b>	<b>0.005</b>	<b>0.04</b>


LHC is one of the first hadron colliders that features useful SR light!

Higher energy machines will face the challenge of significant SR light in a superconducting environment!!!

## SR inside SC Magnet and Beam Vacuum

- If hitting the cold bore of the magnets, the heat deposition of the SR photons will have to be compensated / cooled at 1.9K!






## in the LHC



tipacting and electron cloud build up

or beam instabilities and beam losses



Suppressed with large bunch spacing  
→ 50ns


## Beam Diagnostics: Tune and Chromaticity




- Uncorrected perturbations are about 200 times the required stability!!!
- But change rates are relatively slow → one can foresee a feedback loop, provided one can measure continuously the tune and chromaticity

# BBQ: Diode Based Base Band Tune


AC-coupled



FFT or PLL  
functionalities:





(a) TuneViewer Screen-shot - Beam Spectra




(b) Turn-by-Turn Data


# SR Diagnostics for LHC



## RF INSERTION




# BSRT Hardware Schema





M. Wendt, ICFA mini-Workshop  
on Impedance, Erice 2014


## Gated camera (BSRTS)




# BSRT Operation



...however, the BSRT (particular system B2) showed “unphysical” beam profiles at the start of the operation!





## Extraction Mirror Issues



- Experimented with various mirror material options
  - Si & glass bulk, different coatings, etc.



# Control Room Application



# Run 1 operation: 50ns bunch spacing

■ Electron cloud: strongly suppresses electron cloud effects!

→ reduced beam conditioning times


■ Higher

→ in




CMS Average Pileup, pp, 2012,  $\sqrt{s} = 8$  TeV

2012: ~30 events/xing  
at beginning of fill  
with tails up to ~ 40.




# A nice day at the LHC: 50ns & low intensities



50 bunches @ 50ns per beam → Two OP programmed dumps. About 20 hours in stable beams.

# LS1 Consolidation:





- Total interconnects in the LHC:
  - 1,695 (10,170 high current splices)
- Number of splices redone: ~3,000 (~ 30%)
- Number of shunts applied: > 27,000

## Long Shutdown 1: LS1



### The main 2013-14 LHC consolidations


1695 Openings and final reclosures of the interconnections



Complete reconstruction of 3000 of these splices



Consolidation of the 10170 13kA splices, installing 27 000 shunts



Installation of 5000 consolidated electrical insulation systems



300 000 electrical resistance measurements



10170 orbital welding of stainless steel lines



18 000 electrical Quality Assurance tests



10170 leak tightness tests



3 quadrupole magnets to be replaced



15 dipole magnets to be replaced



Installation of 612 pressure relief devices to bring the total to 1044



Consolidation of the 13 kA circuits in the 16 main electrical feed-boxes





## RunII: Main Concerns with 25ns bunch spacing operation:

- Higher beam intensities and stored beam energies
- Higher electro-magnetic energy in the magnet system due to higher magnetic fields
- E-cloud scrubbing
- Cryo instability with 144+ bunch trains due to transients in the heat load
- Equipment heating (impedance)
- UFO rate
- QPS boards and R2E → machine availability and efficiency!
- Short circuits in protection diode box due to debris → decision to limit energy in Run 2 and DISMAC for LS2

# UFOs – Unidentified Falling Objects:


- Sudden local losses
- Rise time of the order of 1 ms.
- Potential explanation: dust particles interacting with beam creating scatter losses and showers propagating downstream
- Distributed around the ring – arcs, inner triplets, IRs
- Even without quench, preventive dumps by QPS

$R \sim 10 \mu\text{m}$




## RunII Startup: UFO rates (September)


- ❑ There are many UFOs, a significant number  $> 1\%$  of threshold
  - ❑ 0.07% of all UFOs actually dump the beam
- ❑ Slight signs of conditioning when normalizing rate by the total number of bunches



## UFO conditioning in Run2 compared to 2022




## UFO rate 2015 vs 2022



- In general, situation much better than in Run 2 due to the very fast conditioning of the UFO rate
- But the impact of UFOs evidently depends on the BLM threshold strategy

# Radiation to Electronics R2E and Beam Aborts




**Required:**

→ Additional  
Shielding

→ Relocation of  
electronics racks in  
the tunnel

# LHC machine sectorisation





- For superconducting magnets, no DC powering across IPs
- Main DC power feed at even points (MB, MQ), some DC power feed at odd points
- 8 main dipole + 16 quadrupole circuits in LHC

- Commissioning possible for each sector independent of other sectors
- More complex powering system and tracking between sectors



## Hardware Commissioning: Dipole training

- 154 dipoles per sector, powered in series
- Ramp the current until single magnet quenches - “training quench”
- Usually quench 3 – 4 other dipoles at the same time
- Cryogenics recovery time: 6 – 8 hours
- RB34 earth fault → controlled burn off using capacitive discharge







## Connection side of MB and diode




# Metal chips and pieces found in the past



# Training quenches RB Circuits



## Training history RB.A23



- The 64 quenches in S23 after the 2<sup>nd</sup> additional TC came as a surprise, as usually training goes faster after a TC
- Detailed analysis of the dipole training campaigns is ongoing, including results from reception tests in SM18.

# Total number of quenches in LHC main dipoles

Nr of quenches in the same dipole magnet	Nr of dipole magnets
5	3
4	11
3	56
2	154
1	446
0	562




## Conclusion:

- Still 562 dipole magnets (45%) never experienced a training quench in the LHC since 2008.
- Some circuits (including corrector circuits) showed much longer training than in previous campaigns, and their behavior will be closely monitored in the coming years.
- Desired operating currents can still be reached (with only a few exceptions) 14 years after the start of the LHC, with several thermal cycles, numerous current cycles, radiation, and large number of quenches.
- a quench is a very violent process (especially in the high-current circuits), and that each quench implies a certain unavoidable risk (short-to-gnd, internal short, quench heater failure, etc).
- Decision of collision energy post LS3 will inevitably involve a cost/benefit analysis of required re-training effort (which implies technical risks and considerable time!)

# An extra boost from the injectors

The LHC performance fully relies on the **BCMS** - was put in place in the PS

- By itself can achieve diverse and → Higher than nominal beam brightness!




Performance limited by LHC cooling power!!!

[triplet and arc e-cloud]

→  $L < 2.2 \cdot 10^{34} \text{ cm}^{-2} \text{ s}^{-1}$

→  $L > 1.75 \cdot 10^{34} \text{ cm}^{-2} \text{ s}^{-1}$



# LIU beams from the injector complex




LHC Injectors Upgrade

## Hybrid beam: used in 2023

- Interleaving “8 bunches 4 empty slots” (8b4e) with standard 25 ns beam
- As a mitigation of e-cloud and cryo heat load


## Standard 25 ns beam: used early 2024

- Used for beam commissioning with 3x36b trains
- Intensity:  $(1.6-1.65)\times 10^{11}$  p/b at injection



## BCMS beam: used since mid-2024

- PS producing this high brightness beam using the “batch compression, merging, and splitting” scheme
- Intensity:  $(1.6-1.65)\times 10^{11}$  p/b at injection
- Longest batches: 3x36b (2024) and 4x36b (2025)
- Significant work on reducing tails and emittance blow-up



## The less expected...

2/2

### BIRDS & WEASELS

- Electrical fault in 66kV surface substation
- Mitigated by repair and additional protection



### PS MAIN POWER SUPPLY


- Short in capacitor storage bank
- Mitigated by network reconfiguration and operation of rotating machine



### SPS BEAM DUMP

- Limited to 96 bunches per injection
- 2076 (2200) bunches per beam cf. 2750
- Replacement during EYETS






# LHC / HL-LHC Plan



EU funded HiLumi  
Design Study

Approval of  
HL-LHC Project  
LHC





We found a new particle

But still have many questions!

# Questions?


## Technology Challenge: Magnets for High energy

- Nominal LHC triplet: 210 T/m, 70 mm coil aperture
  - ➔ ca. 8 T @ coil
  - ➔ 1.8 K cooling with superfluid He (thermal conductivity)
  - ➔ current density of 2.75 kA / mm<sup>2</sup>
- At the limit of NbTi technology (HERA & Tevatron ca. 5 T @ 2kA/mm<sup>2</sup>)!!!

LHC Production in collaboration with USA and KEK




Critical Surface for NbTi



## Performance Optimization: 2 Competing Effects:

- Discoveries: production of new particles requires CM energy above the production threshold:  $Z \rightarrow 45\text{GeV}$ ,  $W \rightarrow 80\text{GeV}$ ,  $H \rightarrow 125\text{GeV}$   
→ discovery of the unknown implies highest possible CM energy!
- Production rate: cross section decreases with particle mass!




## Performance Optimization: 2 Competing Effects:

Beam Burn off: total cross section increases with CM Energy!!!

→ The beam lifetime decreases with increasing Luminosity AND E

→ Shorter fills which imply reduced efficiency and reduced integrated Luminosity


→ Increased background in the detectors!




## Hadron Collider Limitations / Challenges:

- Beam energy and luminosity:  
→ Beam lifetime and operation efficiency
- Event rate and pile up:  
[number of events per luminous region length]  
→ Detector challenge and efficiency and data quality
- Beam energy and intensity = beam power & stored EM energy  
→ Damage potential and machine protection
- Debris from the IP  
→ Quench protection; heat load and radiation damage
- Beam energy:  
→ Magnet technology [maximum B] and accelerator size & FQ

# THE HL-LHC MAGNET ZOO:



# DS collimators – 11 T Dipole



## Example LEP: SR limit

- physics:  $LEP1 = 45.6\text{GeV}$ ;  $LEP2 = 80.5\text{GeV}$ ;  $LEP_{\text{end}} > 100\text{GeV}$   
 $m_Z = 91\text{GeV}$        $m_W = 91\text{GeV}$        $m_H = 125\text{GeV}$
- LEP Tunnel: circumference = 27 km (ca. 17mi)  
with 22 km arcs (ca. 14mi)
- LEP limitations:
  - $P_{\text{SR}} > 20\text{MW}$
  - $E_{\text{turn}} > 2.8\text{GeV}$
  - $P_{\text{RF}} > 40\text{kW} (> 10\text{MW})$



# Synchrotron Radiation in Superconducting Magnets

## High synchrotron radiation load of protons @ 50 TeV:

- **~30 W/m/beam (@16 T)** (LHC <0.2W/m)
- **5 MW total in arcs**


## New Beam screen with ante-chamber

- absorption of synchrotron radiation at 50 K to reduce cryogenic power
- avoids photo-electrons, helps vacuum



# Past, Present, Future

## Livingston Plot:



# Accelerator for Particle Physics: Goals

## ■ Luminosity Frontier:

- Luminosity and Beam lifetime (>> than fill time)
  - accelerator size, total number of particles, burn-off!!!
  - Data density & cleanliness: luminous region and pileup
- Beam intensity and stored beam energy
- Detector background
- Operation efficiency

- Challenging operation modes at luminosity frontier

# Accelerator for Particle Physics: Goals

## ■ Luminosity Frontier:

- Luminosity and Beam lifetime
- accelerator size, total number of particles, burn-off!!!
- Data density and cleanliness: luminous region and pileup
- Beam intensity and stored beam energy for Hadron beams
- 500MJ!! / beam for HL-LHC
- Operation efficiency

## ■ Energy Frontier:

- Technology driven / limited!!!



# Phase 1 Intensity Limit vs Loss Rate at 7 TeV

*Loss map simulations and LHC design values*

